

BRICKGUN AMMUNITION

9mm

- 1x [Black Cap]
- 2x [Yellow Spacer]
- 1x [Yellow Body]

Assembly diagram for 9mm ammunition. The diagram shows a black cap being placed on top of two yellow spacers, which are then placed on top of a yellow body. Red arrows indicate the direction of assembly. The finished 9mm round is shown to the right.

9mm Hollow Point

- 1x [Yellow Spacer]
- 1x [Black Cap]
- 1x [Black Hollow Point]
- 1x [Yellow Body]

Assembly diagram for 9mm Hollow Point ammunition. The diagram shows a black cap being placed on top of a yellow spacer, which is then placed on top of a black hollow point, which is finally placed on top of a yellow body. Red arrows indicate the direction of assembly. The finished 9mm Hollow Point round is shown to the right.

9mm Hollow Point v2.0

- 1x [Yellow Spacer]
- 1x [Black Cap]
- 1x [Grey Hollow Point]
- 1x [Yellow Body]

Assembly diagram for 9mm Hollow Point v2.0 ammunition. The diagram shows a black cap being placed on top of a yellow spacer, which is then placed on top of a grey hollow point, which is finally placed on top of a yellow body. Red arrows indicate the direction of assembly. The finished 9mm Hollow Point v2.0 round is shown to the right.

10mm

- 1x [Grey Hollow Point]
- 1x [Black Cap]
- 1x [Yellow Body]
- 1x [Yellow Spacer]

Assembly diagram for 10mm ammunition. The diagram shows a black cap being placed on top of a grey hollow point, which is then placed on top of a yellow body, which is finally placed on top of a yellow spacer. Red arrows indicate the direction of assembly. The finished 10mm round is shown to the right.

10mm v2.0

- 1x [Black Cap]
- 2x [Yellow Body]

Assembly diagram for 10mm v2.0 ammunition. The diagram shows a black cap being placed on top of a yellow body, which is then placed on top of another yellow body. Red arrows indicate the direction of assembly. The finished 10mm v2.0 round is shown to the right.

10mm Hollow Point

- 1x [Yellow Body]
- 1x [Yellow Spacer]
- 1x [Black Cap]

Assembly diagram for 10mm Hollow Point ammunition. The diagram shows a black cap being placed on top of a yellow body, which is then placed on top of a yellow spacer. Red arrows indicate the direction of assembly. The finished 10mm Hollow Point round is shown to the right.